Appendix B – Best Management Practices

BMP SC11	LAVATORY SERVICE OPERATION	
PURPOSE: Eliminate discha aircraft lavatory	arges to the storm drain system associated with ground servicing of facilities.	TARGETED ACTIVITIES: → Aircraft Lavatory Service → Lavatory Truck/Cleanout Backflushing
POLLUTION PREVENTION:		POLLUTANTS of CONCERN:
	Implement the following pollution prevention practices and BMPs to prevent discharges to the storm drain system associated with ground servicing of aircraft lavatory facilities: Use only surfactants and disinfectants approved for discharge to the sanitary sewer system.	 → Lavatory Chemicals → Lavatory Waste → Lavatory Truck Wash Water
OPERATIONS	: :	APPLICABLE TENANTS/ DEPARTMENTS:
Sub-BMPs - 01	Triturator facilities are covered and have low roll-over type berming.	→ ACE
- 02 🔲	Triturator facilities should not be located directly in the path of storm drains.	 → Air Canada → Alaska → Allegiant → American Airlines → Avis → British Airways → Delta → DHL → FedEx → Frontier
- 03 🔲	Perform regular inspections of all hoses and fittings used for transferring lavatory waste and keep the equipment in good condition.	
- 04 🔲	Absorbent booms, spill kits and other containment equipment are present on lavatory service equipment and at the triturator facility.	
- 05 🗌	Perform all mixing and transfers of surfactants and disinfectants within the covered and bermed triturator area or under a cover.	→ Hawaiian→ JAL→ JetBlue
- 06 🗌	Use drip pans when draining aircraft lavatory systems. Immediately dump the collected drippage into the bulk storage tank on the lavatory service cart or lavatory service truck.	→ Lufthansa→ SDCRAA→ Signature
- 07 🗌	Immediately clean and properly dispose of all spills of lavatory wastes and lavatory chemicals at the triturator facility.	→ Southwest→ Spirit→ Sun Country
- 08 🗌	Secure all hoses, valves, and equipment when transporting lavatory waste.	→ United → UPS → WestJet
- 09 🗌	Perform lavatory truck cleanouts/backflushing and lavatory waste discharging to sanitary sewer connections ONLY at triturator facilities.	
- 10 🗌	Completely drain all hoses.	
- 11 🗌	Use lavatory service cart or truck with spill prevention equipment installed, where possible.	

Appendix B – Best Management Practices

BMP SC11	LAVATORY SERVICE OPERATION	
- 12 🗌	Temporary sanitary facilities must have secondary containment and be located away from watercourses, drainage facilities, traffic circulation and high wind areas.	
- 13 🗌	Regularly inspect temporary sanitary facilities for leaks and spills and clean or replace when necessary.	
STRUCTURAL TREATMENT BMPs: Refer to BMP TC01 for information on structural treatment BMPs.		
BMP FREQUENCIES/EQUIPMENT/TOOLS: Lavatory service operations occur on a daily basis. Equipment/tools to implement BMPs include secondary containment, bermed areas, overhead cover at triturator, drip pans, spill kits, and drums.		
AUTHORIZED LOCATIONS FOR LAVATORY SERVICE OPERATIONS:		
	Use only the designated areas for ground servicing of aircraft lavatory facilities as shown in the attached map.	
Date:		Version: 2.0

Appendix B - Best Management Practices

Intentionally Left Blank

